MARATHON EQUIPMENT COMPANY



RJ-250 SC Ultra[®] Self-Contained Compactor/Container 15 to 34 Cubic Yard Capacity

Ideal For...

■ MALLS ■ SUPERMARKETS ■ LARGE RESTAURANTS ■ HOTELS ■ HOSPITALS AND INSTITUTIONS






■ Large 41" x 58" feed opening to handle large, bulky items

- Full Door Seal with "P" Seal
- Bubble Gate with "Auto Relatch" and Double-Hinge
- Qwik Clean Tank®
- CYCON Life-Xtender® Cyclic Control System





Dimensions not shown: $8' - 4 \frac{1}{8}" (2543 \text{mm})$ Overall Width **Ground Roller Widths:** $61 \frac{7}{8}" (1572 \text{mm})$ Inside Rollers

67 3/8" (1712mm) Roller Centers 72 7/8" (1851mm) Outside Rollers

RJ-250SC Ultra	Α	В	С	D**	E	WEIGHT
15 cu yds	4' – 0"	3' - 7-1/4"	5' – 7 1/2"	14' – 3"	7' – 5"	8360 lbs
	1219 mm	1099 mm	1715 mm	4344 mm	2261 mm	3792 <i>kg</i>
20 cu yds	4' – 0"	3' - 7-1/4"	5' – 7 1/2"	17' – 4"	7' – 5"	8860 lbs
	1219 mm	1099 mm	1715 mm	5284 mm	2261 mm	<i>4019 kg</i>
25 cu yds	4' – 0"	3' - 7-1/4"	5' – 7 1/2"	17' – 10 1/2"	8' – 8"	9270 lbs
	1219 mm	1099 mm	1715 mm	5449 mm	2642 mm	<i>4205 kg</i>
30 cu yds	4' – 0"	3' - 7-1/4"	5' – 7 1/2"	20' – 5"	8' – 8"	9715 lbs
	1219 mm	1099 mm	1715 mm	6223 mm	2642 mm	<i>4407 kg</i>
34 cu yds	4' – 0"	3' – 7-1/4"	5' – 7 1/2"	22' – 5"	8' – 8"	10100 lbs
	1219 mm	1099 mm	1715 mm	6833 mm	2642 mm	<i>4582 kg</i>

RJ-250SC ULTRA FEATURES:

- Big 41" x 58" feed opening to handle large, bulky items!
- Continuous feed capability even while compactor is operating!
- Adaptable to special loading systems such as large capacity hoppers, security chutes or total enclosures.
- Total odor and pest control via Marathon's Ozone Odor Control option.
- Easy loading from either ground or dock level.
- Over 24 tons of crushing force to reduce refuse to a fraction of its former size saving valuable space.
- Easy and fast installation! Installation costs are cut in half over conventional compaction systems.
- Fire hose connection provided on each unit.
- Factory testing to assure leakproof construction.
- UL Listed.

Specifications:

Charge Box Capacity		
[Mfrs. Rating]	1.7 cu yd	1.3 m³
[WASTEC Rating]	1.31 cu yd	1.0 m ³
Total Capacity	34 cu yd	25.9 m³
Clear Top Opening	41"L x 58"W1016 m	nm x 1041 mm
Loading Height	48"	1219 mm

Performance Characteristics:

Cycle Time	33 s	33 s
Total Normal Force	39,900 lb	177 kN
Total Maximum Force	49,500 lb	220 kN
Normal Ram Face Pressure	27.1 psi	187 kPa
Maximum Ram Face Pressure	33.7 psi	232 kPa
Ram Penetration	6"	152 mm

Electrical Equipment:

Electric Motor 3/60/208-230/460	10 hp	7.5 kW	
Electric Control Voltage	120 VAC	120 VAC	
Panel Box Assembly			
UL Rated	Key Operated		
All Circuits Fused - 3 Push Button Station Start/Stop/Reverse			

Hydraulic Equipment:

Hydraulic Pump	10 gpm	37.85 L/min
Normal Pressure		
Maximum Pressure	2300 psi	158.6 bar
Hydraulic Cylinders (2) - Bore	4"	102 mm
	2-1/2"	

Authorized Distributor:



MARATHON EQUIPMENT COMPANY

P.O. Box 1798 • Vernon, AL 35592-1798 USA • (205) 695-9105 **fax** (205) 695-7250 **1-800-633-8974**130 Hwy. 339 • Yerington, NV 89447 USA • (775) 463-4030 **fax** (775) 463-4531 **1-800-624-5724**1102 Industrial Park Rd. • Clearfield, PA 16830 USA • (814) 765-0200 **fax** (814) 765-2072 **1-800-922-7062**

Visit our web site: www.MarathonEquipment.com

Pictures in this literature are illustrative only. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI Regulation Z245.21, all OSHA standards, and certified under WASTEC's Compactor Certification Program. Products must be used with safe practice and in accordance with said regulations and standards.









